

Flightstar II SC



Standard Equipment

- 60hp HKS 4 Stroke Air Cooled Engine
- Fully Enclosed Cabin with Zippered Sport Doors
- High Lift Wing with Streamlined Struts
- Flightstar Wing Quick Fold System
- Durable Aluminium and Stainless Custom Hardware
- Full Dual Control System
- Anodized Airframe for Corrosion Protection
- 4 Point Pilot Restraint Harness
- Flight and Engine Management Instruments
- In-Flight Adjustable Trim
- 3 Blade Composite Propeller
- Rear Wheel Brakes



Performance

Cruise Speed 128kmph

Max Speed 144kmph

Stall Speed 57.6kmph

Vne 154kmph

Climb Rate 600fpm.

Max Range 250miles

Roll Rate (45 to 45) 2.8sec.

Takeoff Roll 205feet

Glide Ratio (Engine off) 7 to 1.

Sink Rate 450fpm.



Specifications

Wing Span: 32.5ft

Length: 19ft

Wing Area: 162sq ft

Height: 7ft 5in

Aspect Ratio: 6.53

Empty Weight: 220Kgs

MAW: 450kgs

Fuel Capacity: 45 litres

Fuel Consumption: 12-15 litres per hour

Take off distance: 100 meters



No. 111/4, Kaveri Nagar, Hormavu Agrahara Road Cross, Hormavu P.o. Bangalore 560 043

Ph. +91 80 28 44 44 66 Fax +91 28 44 44 84 Mob: +91 99456 51775

E mail: javadhassan@hotmail.com website: www.albatrossflyingsystems.com